

Halliday ♦ Resnick ♦ Walker

**FUNDAMENTALS OF PHYSICS**  
**SIXTH EDITION**

Selected Solutions

Chapter 21

21.9

21.31

21.45

9. (a) The energy that leaves the aluminum as heat has magnitude  $Q = m_a c_a (T_{ai} - T_f)$ , where  $m_a$  is the mass of the aluminum,  $c_a$  is the specific heat of aluminum,  $T_{ai}$  is the initial temperature of the aluminum, and  $T_f$  is the final temperature of the aluminum-water system. The energy that enters the water as heat has magnitude  $Q = m_w c_w (T_f - T_{wi})$ , where  $m_w$  is the mass of the water,  $c_w$  is the specific heat of water, and  $T_{wi}$  is the initial temperature of the water. The two energies are the same in magnitude since no energy is lost. Thus,

$$m_a c_a (T_{ai} - T_f) = m_w c_w (T_f - T_{wi}) \implies T_f = \frac{m_a c_a T_{ai} + m_w c_w T_{wi}}{m_a c_a + m_w c_w}.$$

The specific heat of aluminum is 900 J/kg·K and the specific heat of water is 4190 J/kg·K. Thus,

$$\begin{aligned} T_f &= \frac{(0.200 \text{ kg})(900 \text{ J/kg}\cdot\text{K})(100^\circ\text{C}) + (0.0500 \text{ kg})(4190 \text{ J/kg}\cdot\text{K})(20^\circ\text{C})}{(0.200 \text{ kg})(900 \text{ J/kg}\cdot\text{K}) + (0.0500 \text{ kg})(4190 \text{ J/kg}\cdot\text{K})} \\ &= 57.0^\circ\text{C} \quad \text{or} \quad 330 \text{ K} . \end{aligned}$$

- (b) Now temperatures must be given in Kelvins:  $T_{ai} = 393 \text{ K}$ ,  $T_{wi} = 293 \text{ K}$ , and  $T_f = 330 \text{ K}$ . For the aluminum,  $dQ = m_a c_a dT$  and the change in entropy is

$$\begin{aligned} \Delta S_a &= \int \frac{dQ}{T} = m_a c_a \int_{T_{ai}}^{T_f} \frac{dT}{T} = m_a c_a \ln \frac{T_f}{T_{ai}} \\ &= (0.200 \text{ kg})(900 \text{ J/kg}\cdot\text{K}) \ln \left( \frac{330 \text{ K}}{373 \text{ K}} \right) = -22.1 \text{ J/K} . \end{aligned}$$

- (c) The entropy change for the water is

$$\begin{aligned} \Delta S_w &= \int \frac{dQ}{T} = m_w c_w \int_{T_{wi}}^{T_f} \frac{dT}{T} = m_w c_w \ln \frac{T_f}{T_{wi}} \\ &= (0.0500 \text{ kg})(4190 \text{ J/kg}\cdot\text{K}) \ln \left( \frac{330 \text{ K}}{293 \text{ K}} \right) = +24.9 \text{ J/K} . \end{aligned}$$

- (d) The change in the total entropy of the aluminum-water system is  $\Delta S = \Delta S_a + \Delta S_w = -22.1 \text{ J/K} + 24.9 \text{ J/K} = +2.8 \text{ J/K}$ .

31. (a) If  $T_H$  is the temperature of the high-temperature reservoir and  $T_L$  is the temperature of the low-temperature reservoir, then the maximum efficiency of the engine is

$$\varepsilon = \frac{T_H - T_L}{T_H} = \frac{(800 + 40) \text{ K}}{(800 + 273) \text{ K}} = 0.78 .$$

- (b) The efficiency is defined by  $\varepsilon = |W|/|Q_H|$ , where  $W$  is the work done by the engine and  $Q_H$  is the heat input.  $W$  is positive. Over a complete cycle,  $Q_H = W + |Q_L|$ , where  $Q_L$  is the heat output, so  $\varepsilon = W/(W + |Q_L|)$  and  $|Q_L| = W[(1/\varepsilon) - 1]$ . Now  $\varepsilon = (T_H - T_L)/T_H$ , where  $T_H$  is the temperature of the high-temperature heat reservoir and  $T_L$  is the temperature of the low-temperature reservoir. Thus,

$$\frac{1}{\varepsilon} - 1 = \frac{T_L}{T_H - T_L} \quad \text{and} \quad |Q_L| = \frac{WT_L}{T_H - T_L} .$$

The heat output is used to melt ice at temperature  $T_i = -40^\circ\text{C}$ . The ice must be brought to  $0^\circ\text{C}$ , then melted, so  $|Q_L| = mc(T_f - T_i) + mL_F$ , where  $m$  is the mass of ice melted,  $T_f$  is the melting temperature ( $0^\circ\text{C}$ ),  $c$  is the specific heat of ice, and  $L_F$  is the heat of fusion of ice. Thus,  $WT_L/(T_H - T_L) = mc(T_f - T_i) + mL_F$ . We differentiate with respect to time and replace  $dW/dt$  with  $P$ , the power output of the engine, and obtain  $PT_L/(T_H - T_L) = (dm/dt)[c(T_f - T_i) + L_F]$ . Thus,

$$\frac{dm}{dt} = \left( \frac{PT_L}{T_H - T_L} \right) \left( \frac{1}{c(T_f - T_i) + L_F} \right) .$$

Now,  $P = 100 \times 10^6 \text{ W}$ ,  $T_L = 0 + 273 = 273 \text{ K}$ ,  $T_H = 800 + 273 = 1073 \text{ K}$ ,  $T_i = -40 + 273 = 233 \text{ K}$ ,  $T_f = 0 + 273 = 273 \text{ K}$ ,  $c = 2220 \text{ J/kg}\cdot\text{K}$ , and  $L_F = 333 \times 10^3 \text{ J/kg}$ , so

$$\begin{aligned} \frac{dm}{dt} &= \left[ \frac{(100 \times 10^6 \text{ J/s})(273 \text{ K})}{1073 \text{ K} - 273 \text{ K}} \right] \left[ \frac{1}{(2220 \text{ J/kg}\cdot\text{K})(273 \text{ K} - 233 \text{ K}) + 333 \times 10^3 \text{ J/kg}} \right] \\ &= 82 \text{ kg/s} . \end{aligned}$$

We note that the engine is now operated between  $0^\circ\text{C}$  and  $800^\circ\text{C}$ .

45. (a) Suppose there are  $n_L$  molecules in the left third of the box,  $n_C$  molecules in the center third, and  $n_R$  molecules in the right third. There are  $N!$  arrangements of the  $N$  molecules, but  $n_L!$  are simply rearrangements of the  $n_L$  molecules in the left third,  $n_C!$  are rearrangements of the  $n_C$  molecules in the center third, and  $n_R!$  are rearrangements of the  $n_R$  molecules in the right third. These rearrangements do not produce a new configuration. Thus, the multiplicity is

$$W = \frac{N!}{n_L! n_C! n_R!} .$$

- (b) If half the molecules are in the right half of the box and the other half are in the left half of the box, then the multiplicity is

$$W_B = \frac{N!}{(N/2)! (N/2)!} .$$

If one-third of the molecules are in each third of the box, then the multiplicity is

$$W_A = \frac{N!}{(N/3)! (N/3)! (N/3)!} .$$

The ratio is

$$\frac{W_A}{W_B} = \frac{(N/2)! (N/2)!}{(N/3)! (N/3)! (N/3)!} .$$

- (c) For  $N = 100$ ,

$$\frac{W_A}{W_B} = \frac{50! 50!}{33! 33! 34!} = 4.16 \times 10^{16} .$$